


Features

- Surface mount
- High performance/cost ratio
- Excellent vibration & shock resistance




LC1610

Specification



Type	LC1610	ESR (max.)
Frequency Range fundamental	32,768kHz	32,768kHz = 90K Ohm
Frequency Range over tone	-	
Frequency Tolerance at 25°C±5°C	±20ppm, available ±20ppm ~±50ppm	
Temperature Range	-40°C ~ +85°C, or order code	
Load Capacitance CL	standard 12,5pF; available 9pF	
Shunt Capacitance C0	2pF max.	
Aging	±3ppm/year max.	
Storage Temperature	-55°C - +125°C	Temp. Coefficient at 25°C± 5°C (ppm)
Drive Level	0,1uW max.	-0,045ppm/°C ² max.
RoHS	compliant	
Contents Of Reel	5000 pcs	

Drawing (mm)



Tape dimension (mm)

Soldering profile



Order code

Part	Frequency	Package	Frequency tolerance	Temperature range	Load capacitance	Option
Q	- 32.768000k	- LC1610	- 20	- E	- 12.5	- TR
Q=Quartz	k=kHz	LC1610	±ppm (25°C)	E= -40°C ~ +85°C	12,5 pF 9 pF	TR=Tape and reel X=Special options